Vacuum Pump VP5

The high-performance Vacuum Pump VP5 has been especially developed for the Ivoclar Vivadent ceramic and press furnaces. The pump features a very high delivery rate. In addition, it is characterized by a distinct design and a carrying handle for convenient relocation.

Technical Data:

- Voltage:

Power consumption:Final vacuum:

220- 240 V / 50 - 60 Hz 200 V / 50 - 60 Hz 115 V / 50 - 60 Hz 100 V / 50 - 60 Hz 80 Watt approx. 20 mbar

Colour: Standard colour:

white (no special colours available)



Advantages:

- Modern, ergonomic design
- High vacuum performance
- High final vacuum (approx. 20 mbar **)
- High running smoothness
- Integrated carrying handle

Delivery forms

Vacuum Pump VP5 (white)	230 V/ 50–60 Hz*	666308
Vacuum Pump VP5	1x	
Sound absorber	1x	
Vacuump Pump Filter Kit	1x	

* other voltage versions available ** measured with a 4-liter test container

Vacuum Pump VP3 easy

The small and light-weight VP3 easy vacuum pump is suitable for the evacuation of the firing chamber in lvoclar Vivadent ceramic furnaces. However, the vacuum pump is not suitable for press furnaces. The diaphragm pump is characterized by low weight and extremely small dimensions.

Technical Data:

Standard colour:

Technical Data.	
– Voltage:	230 V / 50 – 60 Hz
	200 V / 50 – 60 Hz
	115 V / 50 – 60 Hz
 Power consumption: 	70 W
 Dimensions: 	W 140 x H 130 x D 210 mm
 Final vacuum: 	approx. 40 mbar
Colour:	

grey

Advantages:

- Light weight
- Small dimensions
- Final vacuum: approx. 40 mbar

Delivery forms

Vacuum Pump VP3 easy (grey)	230 V/ 50-60 Hz*	594554
Vacuum Pump VP3 easy	1x	
Sound absorber	1x	
Vacuump Pump Filter Kit	1x	

* other voltage versions available

